

RAIL PALLET FORKS

Adjustable ITA Class II forged tines.

45.5"
FRAME WIDTH

UP TO
6200 LB
CAPACITY
(VARIES BY MODEL)

42" TO 60"
TINE LENGTHS

1. 3/4" BEVELED RAIL
2. BRICKGUARD FLUSH WITH TINES TO
HELP STABILIZE LOADS
3. BRACING CENTERED ON QUICK TACH FOR
EASY HOOKUP
4. BOLT-ON STEP INSTALLS ON EITHER SIDE

RAIL PALLET FORK –
HI-VIS



- REMOVE CENTER SECTION
TO CHANGE TO A WALK-
THROUGH BRICKGUARD
- 1/4" HIGH
VISIBILITY BRICKGUARD

RAIL PALLET FORK –
WALK-THROUGH



- WALK-THROUGH DESIGN
ALLOWS QUICK CAB ACCESS
- 1/4" HIGH
VISIBILITY BRICKGUARD

RAIL PALLET FORK –
HEX-GUARD



- 3/16" CLASSIC
VIRNIG BRICKGUARD

MODEL	4240	4840	4255	4855	6055	4862
Width: Overall w/ Step / Frame (in.)			50.5 / 45.5			
Overall Height (in.)			37.0			
Tine: Length / Width / Thickness (in.)	42.0 / 4.0 / 1.375	48.0 / 4.0 / 1.375	42.0 / 4.0 / 1.5	48.0 / 4.0 / 1.5	60.0 / 4.0 / 1.5	48.0 / 4.0 / 1.75
Tine Space: Min / Max (in.)			8.8 / 40.9			
Approximate Weight (lbs)	370 ¹	390 ¹	390 ¹	405 ¹	440 ¹	420 ¹
Capacity (lbs)	4000	4000	5500	5500	5500	6200

¹PF model weights listed. Subtract 15 lbs for PFWT model weights. Subtract 25 lbs for PFHG model weights.