

V60 OPEN FRONT ROTARY BRUSH CUTTER

Available widths 72", 78" & 84"

Cuts up to 8" diameter trees. Top of the line cutter with more blades, a heavier flywheel, and industrial grade components to handle the most demanding jobs.




**EAT-N**  
Char-Lynn

Do not operate rotary brush cutter without a shatterproof cab on loader.


<b>8.0"</b> CUT CAPACITY	<b>72" - 84"</b> THREE CUT WIDTHS	<b>20-45 GPM</b> FOUR MOTOR OPTIONS STANDARD & HIGH FLOW	<b>UP TO 610 LB</b> FLYWHEEL WEIGHT	<b>UP TO 2540 LB</b> OVERALL WEIGHT
-----------------------------	---	--	---	--

DETAIL UNDER DECK  
(Shown with Optional Teeth)



**OPTION:  
PRESSURE GAUGE**  
Monitor hydraulic  
operating pressure for  
max productivity.





1. DIRECT DRIVE EATON® MOTOR WITH RELIEF VALVES
2. HYDRAULIC BRAKING STOPS FLYWHEEL WITHIN 10 SECONDS
3. STANDARD MOTOR GUARD & SPINDLE GUARD
4. CIRCULAR FLYWHEEL WITH 4 DOUBLE-SIDED BLADES BOUNCES OFF STUMPS
5. REPLACEABLE AR400 FRONT SKID SHOES & BOLT-ON AR400 BOTTOM DECK RUNNERS

MODEL	IRC72	IRC78	IRC84
Cut Width (in.)	72.0	78.0	84.0
Overall Width (in.)	78.0	84.0	90.0
Overall Height (in.)		27.7	
Overall Depth (in.)	80.0	86.0	92.0
Deck Height (in.)		7.7	
Push Bar Height (in.)		21.7	
Minimum Cut Height (in.)		2.3	
Cutting Capacity, Diameter (in.)		8.0	
Deck Thickness: Top / Side (in.)		0.25 <sup>1</sup>	
Recommended Flow Rate (GPM)	20 – 25 Standard Flow, 25 – 45 High Flow		
Max Operating Pressure (PSI)	3500 Standard / 4100 High Flow		
Approximate Weight (lbs)	2135 <sup>2</sup>	2295 <sup>2</sup>	2470 <sup>2</sup>
Recommended Loader Capacity	Greater than 2200 lbs		
Number of Teeth (Optional)	20	24	28

<sup>1</sup>Material is Grade 50 Plate (50,000 PSI Minimum Yield Strength).

<sup>2</sup>High Flow Motor Options Add Approximately 70 lbs to Model Weight.